

## GT-MPAFF24yS2Y-xM

MTP-APC Female /MTP-APC Female 24-Fiber Method-y Singlemode OS2 9/125 Plenum Cable Yellow- xM



The GigaTech Products **GT-MAPFF24yS2Y-xM** fiber optic patch cord is ideal for short distance patching applications. These fiber optic cables have been built to exceed industry standards and are tested for insertion loss and reflectance on all connectors. They are constructed using Corning glass within UL certified OFNP (Plenum) rated jacket with Kevlar yarn, and are factory terminated resulting in uncompromised performance.

#### **Performance:**

Insertion Loss (max.): <0.60dB

Optical Return Loss: >20dB

Storage Temperature: -40°C +80°C

Operation Temperature: -20°C +70°C

Attenuation dB/km max.: 1.0

### Fiber:

Core Diameter: 9µm

Cladding Diameter: 125µm

Inner Strength Material: Kevlar

Connector Type (1): MTP/F APC

Connector Style(1): Single

Connector Type (2): MTP/F APC

Connector Style (2): Single


#### Jacket:

Jacket Size: 3.5mm

Jacket Style: Multifiber PVC

Jacket Color: Yellow

Fire Rating: OFNP (Plenum)



1	Mode	Ferrule	Housing	Boot	Сар
	SM	24 Fiber SM APC Low Loss	Yellow(PBT)	Black(TPR)	Black(TPR)

2	Category	Jacket O.D.	Jacket Material	Color
	G.65781(9/125um)	Ø3.50mm	PVC OFNP	Yellow



**GT-MPAFF24yS2Y-xM**MTP-APC Female /MTP-APC Female 24-Fiber Method-y Singlemode OS2 9/125 Plenum Cable Yellow- xM

# **Cable Polarity Options** MTP 1 MTP 2 24-Pin METHOD A KEY UP **KEY DOWN** MTP-24 Connector Fiber Assignments PIN OUT MTP 1 MTP 2 24-Pin METHOD B KEY UP KEY UP MTP-24 Connector Fiber Assignments PIN OUT MTP 2 MTP 1 24-Pin METHOD C KEY UP **KEY DOWN** PIN OUT METHOD "C" KEY UP - KEY DOWN (CROSS PAIR) MTP 1 MTP DN MTP 2 MTP-24 Connector Fiber Assignments

www.gigatechproducts.com